

DOW CORNING 200(R) FLUID, 10,000 CST.**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER****1.1 Product Details**

Product Name: DOW CORNING 200(R) FLUID, 10,000 CST.
Other Name: Silicone
Company Product Code: 01013351
Proper Shipping Name: **Not applicable.**
Recommended Use: Intermediate for Dow Corning Internal Use.
 General purpose
 Processing aid
 Ap/deo, silicones for ap/deo
 Cosmetic additive
 Hair care, colorants
 Hair care, conditioners
 Hair care, hair care fixatives
 Hair care, permanents
 Hair care, shampoos
 Skin care, color cosmetics/makeup - eyes
 Skin care, color cosmetics/makeup - lips
 Skin care, moisturizers/sun care

1.2 Company Details

Manufacturer/Supplier: Dow Corning Australia Pty Ltd
Address: 3 Innovation Road, North Ryde, NSW 2113, Australia
Telephone Number: 1300-360-732
Emergency Telephone Number: 1300-360-732

2. HAZARD IDENTIFICATION

- 2.1 Hazard Classification:** Non-Hazardous Substance. Non-Dangerous Goods.
2.2 Risk Phrase(s): Not hazardous.
2.3 Safety Phrase(s): Avoid contact with eyes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion %</u>
Ingredients determined not to be hazardous to 100%		

4. FIRST AID MEASURES**4.1 First Aid Measures:**

Ingestion: Get medical attention.
Eye: Immediately flush with water.

DOW CORNING 200(R) FLUID, 10,000 CST.

Skin: No first aid should be needed.
Inhalation: No first aid should be needed.

4.2 Medical Attention and Special Treatment Needed:

First Aid Facilities: None should be required.
Comments: Treat symptomatically.
Note to physicians: Treat Symptomatically. For further information, the Medical Practitioner should contact Dow Corning Australia Pty Ltd.

5. FIRE FIGHTING MEASURES

- 5.1 Suitable Extinguishing Media:** On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
- 5.2 Hazards From Combustion Products:** Silicon dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.
- 5.3 Precautions For Fire Fighters and Special Protective Equipment:** Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.
- 5.4 Hazchem Code:** **Not applicable.**

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Emergency Procedures:** Not applicable.
- 6.2 Methods and Materials for Containment and Clean Up Procedures:** Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

- 7.1 Precautions for Safe Handling:** Use with adequate ventilation. Avoid eye contact. Do not take internally. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking. If this product is heated to > 150 degrees C, trace quantities of formaldehyde may be released, and adequate ventilation is required.

DOW CORNING 200(R) FLUID, 10,000 CST.

7.2 Conditions for Safe Storage: Use reasonable care and store away from oxidizing materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Standards:

Ingredients

None known.

Exposure Limits

8.2 Engineering Controls:

Local Ventilation: None should be needed.
General Ventilation: Recommended.

8.3 Personal Protective Equipment:

Respiratory: No respiratory protection should be needed.
Suitable Respirator: None should be needed.
Hand: No special protection needed.
Eye: Use proper protection - safety glasses as a minimum.
Skin: Washing at mealtime and end of shift is adequate.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Form: Viscous Liquid
9.2 Colour: Colorless
9.3 Odour: Characteristic odor
9.4 pH: Not determined.
9.5 Vapour Pressure @ 25°C: Not determined.
9.6 Vapour Density (air=1): Not determined.
9.7 Boiling Point: > 65 °C
9.8 Melting Point: Not determined.
9.9 Solubility in Water: Not determined.
9.10 Specific Gravity @ 25°C: 0.97
9.11 Flash Point: > 100 °C (Closed Cup)
9.12 Upper Flammability Limit: Not determined.
9.13 Lower Flammability Limit: Not determined.
9.14 Autoignition Temperature: Not determined.
9.15 Viscosity: 10000 cSt

DOW CORNING 200(R) FLUID, 10,000 CST.

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

- 10.1 **Chemical Stability:** Stable.
- 10.2 **Conditions to avoid:** None.
- 10.3 **Incompatible Materials:** Can react with strong oxidising agents.
- 10.4 **Hazardous Decomposition Products:** Silicon dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.
- 10.5 **Hazardous Reactions :** Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

- 11.1 **Possible Routes of Exposure** Inhalation Skin Contact Ingestion

11.2 **Possible Health Effects:**Acute

- Ingestion:** Low ingestion hazard in normal use.
- Eye:** Direct contact may cause temporary redness and discomfort.
- Skin:** No significant irritation expected from a single short-term exposure.
- Inhalation:** No significant effects expected from a single short-term exposure.

Chronic

- Ingestion:** Repeated ingestion or swallowing large amounts may injure internally.
- Skin:** No known applicable information.
- Inhalation:** No known applicable information.
- Other Health Hazard Information:** No known applicable information.

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 **Environmental Fate and Distribution:**

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.2 **Ecotoxicity:**

DOW CORNING 200(R) FLUID, 10,000 CST.

No adverse effects on aquatic organisms.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

12.4 Additional Environmental Information

Degradation: Additional environmental information on the silicone component is available on request.

13. DISPOSAL CONSIDERATIONS

13.1 Disposal Method: Dispose of in accordance with local regulations.

13.2 Special Precautions for Landfill or Incineration: None known.

14. TRANSPORT INFORMATION

14.1 UN No.: Not applicable.

14.2 Proper Shipping Name: Not applicable.

14.3 Class: Not applicable.

14.4 Packing Group: Not applicable.

14.5 Hazchem Code: Not applicable.

14.6 Sea transport (IMDG)
Not subject to IMDG code.

14.7 Air Transport (IATA-DGR)
Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 SUSDP Poisons Schedule Number: None allocated.

15.2 Prohibition/Licensing Requirements: There are no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

15.3 Industrial Chemicals (Notification and Assessment) Act 1989: All ingredients listed or exempt.

DOW CORNING 200(R) FLUID, 10,000 CST.**15.4 Chemical Inventories:**

DSL:	All chemical substances in this material are included on or exempted from the DSL.
IECSC:	All ingredients listed or exempt.
EINECS:	All ingredients listed or exempt.
MITI:	All components are listed on ENCS or its exempt rule.
KECL:	All ingredients listed, exempt or notified.
PICCS:	All ingredients listed or exempt.
TSCA:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

16. OTHER INFORMATION

Contact Point: Product Safety Manager - 1300-360-732

Prepared by: Dow Corning Australia Pty Ltd

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this Company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

(R) indicates Registered Trademark